SAFETY DATA SHEET



Date of issue/Date of revision 21 February 2020 Version 2.08

Section 1. Identification		
Product code	: 00290291	
Product name	: SIGMAGUARD 750 PIGMENT	
Product type	: Powder.	
Relevant identified uses of Identified uses Coating. Paints. Painting-re	f the substance or mixture and uses advised against	
Supplier's details	: ₱PG Industries (Singapore) Pte. Ltd., No. 1 Tuas Basin Close, Singapore 638803. Tel +65 68653737	
Emergency telephone number (with hours of operation)	: CHEMTREC +(65)-31581349 (CCN 17704)	

Classification of the substance or mixture	: AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1	
GHS label elements, including precautionary statements		

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Very toxic to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	Avoid release to the environment.
Response	:	Collect spillage.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Singapore	English (US)	Page: 1/11
-----------	--------------	------------

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

CAS number/other identifiers

CAS number	: Not applicable.
EC number	: Mixture.

Ingredient name %	%	CAS number
		7440-66-6 1314-13-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects			
Eye contact	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.	е	
Inhalation	Exposure to airborne concentrations above statutory or recommended exposur limits may cause irritation of the nose, throat and lungs.	е	
Skin contact	No known significant effects or critical hazards.		
Ingestion	No known significant effects or critical hazards.		
Over-exposure signs/symptoms			
Eye contact	Adverse symptoms may include the following: irritation redness		
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing		
Skin contact	No specific data.		
Ingestion	No specific data.		

Singapore	English (US)	Page: 2/11
Singapore		

Section 4. First aid measures

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures Extinguishing media Suitable extinguishing : Use dry chemical powder. media Unsuitable extinguishing : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. media Specific hazards arising : May form explosible dust-air mixture if dispersed. This material is very toxic to aquatic from the chemical life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. **Hazardous thermal** : Decomposition products may include the following materials: decomposition products metal oxide/oxides oxides of lead **Special protective actions** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable for fire-fighters training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. **Special protective** : Fire-fighters should wear appropriate protective equipment and self-contained equipment for fire-fighters breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	-	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Product name SIGMAGUARD 750 PIGMENT

Section 6. Accidental release measures

Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for cont	ainment and cleaning up
Small spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid release to the environment. Refer to special instructions/safety data sheet. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general : occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits
Z înc oxide		Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 10 mg/m ³ 8 hours. Form: Dust PEL (short term): 10 mg/m ³ 15 minutes. Form: Fume PEL (long term): 5 mg/m ³ 8 hours. Form: Fume
Recommended monitoring procedures	atmosphere or biological mo of the ventilation or other con protective equipment. Refer standards. Reference to national	dients with exposure limits, personal, workplace onitoring may be required to determine the effectiveness ntrol measures and/or the necessity to use respiratory rence should be made to appropriate monitoring tional guidance documents for methods for the substances will also be required.
Appropriate engineering controls	vapor or mist, use process e controls to keep worker expo or statutory limits. The engir	ilation. If user operations generate dust, fumes, gas, inclosures, local exhaust ventilation or other engineering osure to airborne contaminants below any recommended neering controls also need to keep gas, vapor or dust wer explosive limits. Use explosion-proof ventilation
Environmental exposure controls	they comply with the require cases, fume scrubbers, filter	r work process equipment should be checked to ensure ments of environmental protection legislation. In some s or engineering modifications to the process equipment emissions to acceptable levels.
ndividual protection measure	<u>es</u>	
Hygiene measures	eating, smoking and using th Appropriate techniques shou	face thoroughly after handling chemical products, before ne lavatory and at the end of the working period. In the used to remove potentially contaminated clothing. If before reusing. Ensure that eyewash stations and the workstation location.
Eye/face protection	: Safety glasses with side shie	elds.
Singapore English (US)		Page: 5/11

Product name SIGMAGUARD 750 PIGMENT

Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Appearance	
Physical state	: Solid. Powder.
	Fowder.
Odor	: Odorless.
рН	insoluble in water.
Flash point	: Closed cup: Not applicable.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Vapor pressure	: Highest known value: 1e-008 kPa (8e-008 mm Hg) (at 20°C) (Zinc powder - zinc dust (stabilized)).
Vapor density	: Highest known value: 5.47 (Air = 1) (zinc oxide).
Relative density	: 7.14
Solubility	: Insoluble in the following materials: cold water.
Auto-ignition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Hazardous decomposition products	: Evolves hydrogen on contact with water. Depending on conditions, decomposition products may include the following materials: metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient nan	ne	Result	Species	Dose	Exposure
Zinc powder - zinc dust (stabilized)		LC50 Inhalation Dusts and mists	Rat	>5.4 mg/l	4 hours
· · · · ·		LD50 Oral	Rat	>2000 mg/kg	-
zinc oxide		LC50 Inhalation Dusts and mists	Rat	>5700 mg/m³	4 hours
		LD50 Dermal	Rat	>2000 mg/kg	-
		LD50 Oral	Rat	>5000 mg/kg	-
Conclusion/Summary	11	There are no data available on the	mixture itself.		
rritation/Corrosion					
Conclusion/Summary					
Skin	10	There are no data available on the	mixture itself.		
Eyes	: 1	There are no data available on the	mixture itself.		
Respiratory	10	There are no data available on the	mixture itself.		
<u>Sensitization</u>					
Conclusion/Summary					
Skin	10	There are no data available on the	mixture itself.		
Respiratory	10	There are no data available on the i	mixture itself.		
<u>Mutagenicity</u>					
Conclusion/Summary	:	There are no data available on the	mixture itself.		
Carcinogenicity					
Conclusion/Summers	:	There are no data available on the	mixture itself.		
Conclusion/Summary					
Conclusion/Summary Reproductive toxicity Conclusion/Summary	:	There are no data available on the	mixture itself.		

Singapore	English (US)	Pa
-----------	--------------	----

Carcinogenicity

English (US)

Mutagenicity

Singapore

Page: 8/11

Product name SIGMAGUAR	D 750 PIGMENT
Section 11. Toxic	ological information
Conclusion/Summary	There are no data available on the mixture itself.
Specific target organ toxici	<u>ty (single exposure)</u>
Not available.	
Specific target organ toxici Not available.	t <u>y (repeated exposure)</u>
Aspiration hazard Not available.	
Information on the likely routes of exposure	: Not available.
Potential acute health effect	<u>S</u>
Eye contact	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
	ysical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: No specific data.
Ingestion	: No specific data.
	cts and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	
General	: Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation.

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

Ocation 44. Torris also visal informa

Section 11. Toxicological information

Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Product/ingredient name	Result	Species	Exposure
Zínc powder - zinc dust (stabilized)	Acute EC50 0.106 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
. ,	Chronic NOEC 0.0727 mg/l Fresh water	Daphnia - Daphnia Magna	21 days
zinc oxide	Acute EC50 0.17 mg/l	Algae	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna -	48 hours
		Neonate	
	Chronic NOEC 0.017 mg/l Fresh water	Algae	72 hours

Section 12. Ecological information

Persistence/degradability

Not available.

Tovioltu

Conclusion/Summary : There are no data available on the mixture itself.

Bioaccumulative potential

Singapore	English (US)	Page: 9/11
-----------	--------------	------------

Section 12. Ecological information

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

 Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3077	UN3077	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)	(Zinc powder - zinc dust (stabilized), zinc oxide)
Transport hazard class(es)	9	9	9
Packing group	III	III	Ш
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(Zinc powder - zinc dust (stabilized), zinc oxide)	Not applicable.

Additional information

UN

:This product is not regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

Singapore	English (US)	Page: 10/11
-----------	--------------	-------------

Product code 00290291 Product name SIGMAGUARD 750 PIGMENT

FIGURE TIME SIGMAGUARD 750 FIGMENT

Section 14. Transport information

IMDG	:This product is not regulated as a dangerous good when transported in sizes of $\leq 5 L$ or $\leq 5 kg$,
	provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
	The segregation group has been manually assigned based upon product analysis.
ΙΑΤΑ	:This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

Ingredient name	Status
Cadmium and its compounds in controlled EEE	Listed

International regulations

Montreal Protocol

Not listed.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: 21 February 2020
Date of previous issue	: 6/16/2019
Version	: 2.08
Prepared by	: EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Singapore	English (US)	Page: 11/11
-----------	--------------	-------------